

精致型梯形齿橡胶带

H 型



大批量
订购
bulk order

■ H 型

进口
产品



CAD
2D/3D




标准加工

型式	齿面保护层	材质	芯线
HQ-ABRN-H	尼龙帆布	氯丁橡胶	玻璃纤维

产品特点: 小型铣床、割草机、发电机、压缩机、碎边剪切机、钻孔整修机、钻孔机、玻璃制瓶机、食品机器、卷绳机、轧辊、木工机。

▲使用温度 -20~80°C。



HQ-ABRN-H
H 型

订购编号示例

① 代号	-	② 齿形	③ 公称宽度	-	④ 编号
HQ-ABRN	-	H	075	-	45

HQ-ABRN-H (齿距: 12.7mm)					
① 代号	② 齿形	③ 公称宽度	④ 编号	周长 (mm)	齿数
HQ-ABRN	H	075 (19.1mm)	45	571.5	45
			46	584.2	46
			48	609.6	48
			49	622.3	49
			51	647.7	51
			54	685.8	54
			56	711.2	56
			60	762	60
			62	787.4	62
			63	800.1	63
		64	812.8	64	
		66	838.2	66	
		68	863.6	68	
		70	889	70	
		72	914.4	72	
		74	939.8	74	
		75	952.5	75	
		78	990.6	78	
		80	1016	80	
		82	1041.4	82	
		84	1066.8	84	
		86	1092.2	86	
		90	1143	90	
		93	1181.1	93	
		96	1219.2	96	
		98	1244.6	98	
		102	1295.4	102	
		106	1346.2	106	
		108	1371.6	108	
		112	1422.4	112	
114	1447.8	114			
116	1473.2	116			
120	1524	120			
121	1536.7	121			
125	1587.5	125			
126	1600.2	126			
128	1625.6	128			
130	1651	130			
132	1676.4	132			
136	1727.2	136			
140	1778	140			
146	1854.2	146			
150	1905	150			

HQ-ABRN-H (齿距: 12.7mm)					
① 代号	② 齿形	③ 公称宽度	④ 编号	周长 (mm)	齿数
HQ-ABRN	H	075 (19.1mm)	154	1955.8	154
			160	2032	160
			162	2057.4	162
			168	2133.6	168
			170	2159	170
			172	2184.4	172
			176	2235.2	176
			180	2286	180
			190	2413	190
			200	2540	200
		204	2590.8	204	
		220	2794	220	
		224	2844.8	224	
		226	2870.2	226	
		228	2895.6	228	
		230	2921	230	
		232	2946.4	232	
		250	3175	250	
		257	3263.9	257	
		265	3365.5	265	
		269	3416.3	269	
		270	3429	270	
		280	3556	280	
		340	4318	340	
		100 (25.4mm)	200	2540	200
			204	2590.8	204
			220	2794	220
			224	2844.8	224
			226	2870.2	226
			228	2895.6	228
230	2921		230		
232	2946.4		232		
250	3175		250		
257	3263.9		257		
150 (38.1mm)	230	2921	230		
	232	2946.4	232		
	250	3175	250		
	257	3263.9	257		
	265	3365.5	265		
	269	3416.3	269		
	270	3429	270		
	280	3556	280		
	340	4318	340		
	200	2540	200		
204	2590.8	204			