

SpeedRoller



STRONG

A reliable basis for intensive use

Properties

- max. surface area (WxH) = 25 m²
- max. width (W) = 5,000 mm, max. height (H) = 5,000 mm
- wind load resistance class 2 according to EN 12424, or up to 7 Beaufort minimal (50 - 61 km/h)
- opening speed with Frequency Control max. 1.8 m/s*, closing speed approx. 0.5 m/s
- 0.7 mm thick door curtain (1.2 mm optional) in blue, black, white, grey, graphite grey, red, orange or yellow
- various window types available as an option
- designed as an inside door for larger doorways with average wind load
- EN13241 compliant

Wind load resistance*	
Up to 2500 mm	Class 1-2
Up to 4000 mm	Class 2
Up to 5000 mm	Class 0



Intelligent Door Solutions

SpeedRoller **STRONG**

The Strong is the standard rapid roll door for intensively used openings. Proven technology guarantees years of trouble-free operation. All aspects of the door are robustly designed and well-engineered for every day energy saving, draught exclusion and climate control.

Dimensions	
max. width	5,000 mm
max. height	5,000 mm
max. surface area	25 m ²
required lateral space at the guides	175 / 200 mm
required lateral space at slip on drive	300 mm
required lateral space at drive for fitting	410 mm
lateral space at side guide profiles	145 mm
space above	350 mm
Wind load resistance at clear width*	
Up to 2500 mm	Cl. 1-2
Up to 4000 mm	Cl. 1
Up to 5000 mm	Cl. 0

Components and construction

The SpeedRoller Strong is a door without balance springs, consisting of an electrically driven door curtain rolled up on a roller above the opening. The door curtain is made of horizontal sections of extremely durable polyester-reinforced PVC. The sections are fitted with aluminium reinforcement profiles with integrated EndLocks, and can be equipped with various types of vision- or insect netting sections between approx. 1,000 and 2,000 mm height. The bottom of the door curtain has a solid HardEdge bottom beam, a flexible FlexEdge bottom beam is available as an option. U-shaped columns with sideseals ensure lateral guidance of the door curtain. The lateral guides are one unit combined with the bearing plates for secure fastening to the roller and drive.

Materials

The door columns are made of two hot dip galvanised steel profiles. The front covers are removable for fast and simple installation and maintenance. The side seals are specifically tailored to your use. The horizontal roller is steel. The HardEdge bottom beam is aluminium, the optional FlexEdge bottom beam is sturdy but flexible and has a soft outer shell. The door curtain is a 0.7 mm thick PVC with a polyester reinforcement inlay. 1.2 mm fabric optionally available¹.

Colour

The door curtain is available in the colours blue, black, white, grey, graphite grey, red, orange or yellow and provided with a vision section.

Drive

The drive consists of an electric motor with reduction unit. The roller is directly driven. Drive side available left or right (standard).

Technical details electric motor

- mains voltage without frequency control..... 3N~400V/50Hz/16A
- mains voltage with frequency control..... LNPE~230V/50Hz/16AT
- degree of protection IP65
- consumed power max. 2 kW

Protection

- the door can be manually opened in the case of a power loss
- electric motor with reduction unit and built-in roll-off safety
- light curtain up to 2,500 mm high

Performance	
control box without frequency control (standard):	
max. opening speed	0.7 m/s
max. closing speed	0.5 m/s
control box with frequency control (optional):	
max. opening speed	1.8 m/s*
max. closing speed	0.5 m/s

Structural provisions and connection

- a flat mounting frame and the necessary mounting space must be available
- exact installation dimensions in the Technical Datasheet
- within a radius of 500 mm of where the control unit **without** frequency control will be positioned there must be a wall socket:
 - CEE-form red, 3N~400V/50Hz/16A
- within a radius of 500 mm of where the control unit **with** frequency control will be positioned there must be a wall socket:
 - CEE-form blue, 1 x 230V fused, slow operation 16 A fitted with a circuit-breaker of at least 300 mA
- the control box usually is fitted on the drive side, at a height of approx. 1,500 mm from the floor
- with standard CEE-plug, the control box is IP54 compliant

Control and operation

The control unit has 3 buttons (open-stop-close) and a CEE plug, and regulates a multitude of functions such as:

- adjustable open time
- 7-segment display for control of the various functions
- permanently open or permanently shut
- service and run mode

Depending on the size and application of the door you can choose between two types of control:

- Tormatic T100R **without** frequency control
- Tormatic T100R-FU **with** frequency control

Additional controls that can be connected to the control box are:

- push-button, pull switch, key-operated switch, photocell, radar, induction loop detection or radio control. Other forms of operation on request



Available controls:

T100R

T100R FU

Extras ¹

Control and operation

- frequency control
- additional controls as described above
- control box directly wired (control box IP65)
- main switch directly wired on the control box (IP65)
- door interlock control in combination with another door

Protection

- connection of traffic lights (red/green or red and green)
- warning light (orange or red)

Construction

- 1.2 mm thick door leaf
- flexible 'FlexEdge' bottom beam
- window sections made of mosquito netting
- stainless steel columns
- PVC, metal or stainless steel hood (drive cover in PVC only)
- metal hood and PVC drive cover in customer-specified RAL colour

* Depending on the configuration ¹ subject to surcharge



www.novoferm.com

For more information:

Novoferm Nederland BV

Tel.: +31 (0)475 346 162

E-Mail: industrie@novoferm.nl

Internet: www.novoferm.com



Intelligent Door Solutions