

Flat air duct system

for roof-mounted cooling units and air/water heat exchangers, to fit TS 8 enclosures from a width of 800 mm and a depth of 600 mm

Cold air may be routed directly to specific areas of the enclosure using the air duct system. The risk of air short circuits due to self-ventilated installed devices is therefore eliminated.

The flat duct has dimensions of W x H x D 229 x 1500 x 29 mm, and may be shortened to the required length.

Material:

- Flame-resistant plastic to DIN 4102/B1

Colour:

- RAL 7035

Supply includes:

- Flat duct
- Adaptor
- Compensating piece
- Deflector, 90°

Note:

- Do not direct cold air straight at active components
- When using the ducting system, the performance of the heat exchanger may be reduced, depending on the respective application
- Not to be used in conjunction with quick-change frame, see page 384



Also required:

- TS support strips, see page 609



Accessories:

- Deflector 90°, see page 374
- Stopper, see page 376
- Flat duct extension, see page 375

For unit	Packs of	Model No.
3209... /3210... /3273... /3383... /3384... /3385...	1 pc(s).	3286.850

Flat duct extension

Extension kit for air duct system and flat air duct system for width, depth or height length extensions in TS 8 enclosures.

Material:

- Flame-resistant plastic to DIN 4102/B1

Packs of	Model No.
1 pc(s).	3286.860

Supply includes:

- Flat duct 1500 mm
- Connecting piece

